



(8 HEADS)

Profueion

1 PASS - 4800 Mtrs/Day







Sublimation Ink

08*i3200 Heads CMYK



360 x 1200 Dpi - 1pass	320m2/h		
360 x 2400 Dpi - 2pass	180m2/h		

360 x 3600 Dpi - 3pass 120m2/h

www.tpaper.in

Both the sublimation and direct-to-textile printers are examples of our expertise and engineering top performing, reliable and precise. With the TIRUPATI series printer, you can maximize productivity while controlling quality and minimizing cost for beautiful soft signage, apparel, and interior decor items that will set your business apart from the competition. Wide application in clothing, home decoration fabric, samplings, shirt canvas bags, bolster scooter, flags, textile gadgets, etc.











Double high-precision mute rail



Front expander



Rear media balance bar

Stable 5L bulk system

ensures amazing printing



Media retraction tension bar



Jombomedia roll maximum 1000m media load



Inflatable take up and feed media shaft



Frequency motor ensures more stable material loading and take-up

TECHNICAL SPECIFICATIONS

Model		TX-08	
Print Head		08*i3200 Print Heads	
Printing Technology		Piezoelectric Inkjet	
	Width	71.6 in.(1820 mm)	
Acceptable Media	Thickness	Maximum 39 mil(1 mm)	
	Weight	220 lb.(100 kg)	
Printing Width		70.8 in.(1800 mm)	
Ink Cartridges	Туре	Dye Sublimation Ink	
	Capacity	4*4 CISS (220ml ink cartridge with 5L ink tank)	
	Color	4 colors (Cyan, Magenta, Yellow, Black)	
RIP Software		Neostampa 8.9	
Printing Resolution		Maximun 2400 dpi	
		1 pass(360x1200dpi): 320 sqm/h	
Printing Speed		3pass(360x2400dpi): 180 sqm/h	
		3pass(360x3600dpi): 120 sqm/h	
Media Heating System		Intergrated post heater & Infrared Dryer & Fan system	
Interface		USB 3.0	
Power Supply		AC 220V+ 10%, 50/60 HZ	
Dimensions(with stand)		133.86(W)x51.18(D)x74.80(H) in.	
Dimensions(with stand)		(3400(W)x1300(D)x1900(H)mm)	
Weight(with stand)		1212.54 lb. (550 kg)	
Package Dimensions		133.86(W)x55.12(D)x78.74(H)in.	
T dollage Difficitions		(3600(W)x1400(D)x2000(H)mm)	
Package Weight		1455.05 lb.(660kg)	
Environment	Power off	Temperature: 59 *F to 90 *F [15'C to 32 'C] / Humidity: 35 to 80% (no condensation)	
	Power off	Temperature: 41 *F to 104 *F [5'C to 40 'C] / Humidity: 20 to 80% (no condensation)	
Accessories		USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software etc.	

CONTACT US

4 +91 82384 33322		4 +91 99788 00900		4 +91 75738 33322		+91 99788 12212
	i		i		i	

■ sublimationtpaper@gmail.com