



TIRUPATITM
INTERNATIONAL



www.tpaper.in

TX08-2.6 / TX08-3.2

Wider Width Dye Sublimation Printer



Eight i3200 Heads
CMYK

Sublimation Ink



*2.6m Eight i3200 Print Heads Speed

360x1200dpi - 1pass	373 m ² /h
360x2400dpi - 2pass	214 m ² /h
360x3600dpi - 3pass	143 m ² /h

*3.2m Eight i3200 Print Heads Speed


360x1200dpi - 1pass	420 m ² /h
360x2400dpi - 2pass	234 m ² /h
360x3600dpi - 3pass	160 m ² /h

Both the sublimation and direct-to-textile printers are examples of our expertise and engineering top performing, examples of our expertise and engineering top performing, examples of our expertise and engineering top performing, reliable and precise. With the TIRUPATI series printer, you can maximize productivity while controlling quality and minimizing cost for beautiful soft signage, apparel, and interior decor items that will set your business apart from the competition. Wide application in clothing, home decoration fabric, samplings, shirt canvas bags, bolster scooter, flags, textile gadgets, etc.



● Technical Specification

Model	TX08-2.6	TX08-3.2
Print Head	08*3200 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width Thickness Maximum Media Load	103.5 in.(2630 mm) Maximum 39 Mil(1 mm) 3000m
Printing Width	102 in.(2600 mm)	126 in (3200 mm)
Ink Cartridges	Type Capacity Color	Dye Sublimation Ink 4*4 CISS (220ml ink cartridge with 5L Ink tank) 4 colors (Cyan, Magenta, Yellow, Black)
Printing Resolution	Maximum 3600 dpi	
Printing Speed	1pass(360x1200dpi):373 sqm/h 2pass(360x2400dpi):214 sqm/h 3pass(360x3600dpi):143 sqm/h	1pass(360x1200dpi):420 sqm/h 2pass(360x2400dpi):234 sqm/h 3pass(360x3600dpi):160 sqm/h
Media Heating System	Intergrated post heater & Infrared Dryer & Fan system	
Interface	USB 3.0	
Power Supply	AC 220V ± 10%, 50/60 HZ	
Dimensions (with stand)	165.35(W)x51.18(D)x78.74(H) in (4200(W)x1300(D)x2000(H) mm)	179.53(W)x57.09(D)x82.68(H) in (4560(W)x1450(D)x2100(H) mm)
Weight(with stand)	1940 lb. (880 kg)	2205 lb. (1000 kg)
Package Dimensions	173.22(W)x55.12(D)x82.68(H) in (4400(W)x1400(D)x2100(H) mm)	187.40(W)x61.02(D)x86.61(H) in (4760(W)x1550(D)x2200(H) mm)
Package Weight	2161 lb. (980 kg)	2225 lb. (1100 kg)
Environment	Power on Power off	Temperature: 59 °F to 90 °F [15°C to 32°C] / Humidity: 35 to 80% (no condensation) Temperature: 41 °F to 104 °F [5°C to 40°C] / Humidity: 20 to 80% (no condensation)
Accessories		USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.




Double high-precision mute rail



Stable 5L bulk system ensures amazing printing speed




Front expander



Rear media balance bar



Media retraction tension bar



Junbo media roll maximum 1000m media load



Inflatable take up and feed media shaft



Frequency motor ensures more stable material loading and take-up

CONTACT US

+91 82384 33322

+91 99788 00900

+91 75738 33322

+91 99788 12212

✉ sublimationtpaper@gmail.com